



ROSETTA

Espresso, from a new perspctive

Elegance meets sophistication

Welcome to the Rosetta range, built to be elegant and solid, with sophisticated design detail that draws attention to them. Offering several models in the range, ensures that you will always be able to match a model to the right requirements.

You can be sure that all Rosetta machines deliver what they promise. We have combined our genuine experience of building first-class espresso machines with creative solutions and the latest innovative technology.

Perfectly brewed espresso, and steaming hot cappuccinos to please your guests, every day, year after year. Rosetta fits in all types of environments, from small artisan coffee shops to toplevel restaurants.



Features

- Built-in volumetric motor pump, equipped with two retention valves and solid particles filter
- Copper boiler with pressure relief valve
- Boiler draintap (except compact)
- Group head with direct pre-infusion chamber
- Decorative stainless cup rail
- Cool wall stainless steam arms
- Electronic controlled hot water outlet
- Automatic back flush program
- 4 programable doses settings
- · Heating element thermal cut off

Display Features

- Advertising display
- Coffee audit trail
- Daily machine on/off program
- Precision PID boiler control
- Grind quality alarms
- Service period notification
- · Water filter change alarm

Supplied Accessories

- 1 single filter handle all machines
- 2 group, 2 double filter handles
- 3 group, 3 double filter handles
- 0.55 metre water filter hose
- 1.5 metre waste hose
- 1 cleaning membrane
- 1 espresso cup stand

Optional Accessories

Capsule conversion kits

Details



Variants



2 Group Compact



2 Group



3 Group



Specifications	2 group compact	2 group	3 group single phase
Height	20.86 in / 530mm	20.86 in / 530mm	20.86 in / 530mm
Depth	23.22in / 590mm	23.22in / 590mm	23.22in / 590mm
Width	18.11 in / 460mm	27.16 in / 680mm	38.58 in / 980mm
Weight	88 lb / 40 kg	121 lb / 55 kg	160 lb / 73 kg
Brewing Groups	2	2	3
Boiler Volume (Litre)	6	11.5	17.5
Boiler Pressure (Bar)	0.8 to 1.2	0.8 to 1.2	0.8 to 1.2
Total Boilers	1	1	1
Steam Wands	1	2	2
Hot Water Tap	1	1	1
Noise Level	<70dB	<70dB	<70dB
Power Supply	220-240VAC, 50/60Hz, 1N-2780W	220-240VAC, 50/60Hz, 1N-3330W	380-415VAC, 50/60Hz, 3N-6290W
Water Connection	G3/8 Internal thread	G3/8 Internal thread	G3/8 Internal thread



Welbilt offers fully-integrated kitchen systems and our products are backed by KitchenCare® aftermarket parts and service. Welbilt's portfolio of award winning brands includes Cleveland™, Convotherm®, Crem®, Delfeld ®, ftkitchen ®, Frymaster®, Garland®, Kolpak®, Lincoln™, Manitowoc ®, Merco®, Merrychef® and Multiplex®.

Bringing innovation to the table • welbilt.com